



Decorative CP12 STEM H: 13.50 W: 12.50 OAL: 27.25

Description

Prismatic reflexor pendant with 12" stem and 40° swivel canopy

Specifications

Housing Spun aluminum bullet with stamped steel canopy

Diffuser/Optics Bare lamp (no diffuser) for Dry locations only

Light Source	GUL	MBL	Medium Base
Max Watts	15	15	150

Electrical

- MB** - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.
- MBL** - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures.
- GUL** - Includes GU24 base 120V HPF Triac dimmable 25,000 Hr OmniLED A lamp with integrated driver.

Mounting Mounts over 4" recessed outlet box.

Certification Manufactured in accordance with U.L. standard 1598 - For dry locations only



Ordering Guide: Choose from each category, using designated code to specify.

CP12 STEM					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

Diffuser/Optics

Bare-lamp (no diffuser)

Light Source

- MB25 A** - 25W MAX. MED base (A19 lamp by others)
- MBL6A** - 5.5W/30K 470 Lm OmniLED
- MBL9.8A** - 9.8W/30K 800 Lm OmniLED
- MBL10A JAB** - 10W/30K 800 Lm 90+ CRI OmniLED
- MBL11A** - 11W/30K 1100 Lm OmniLED
- GUL11A** - 11W/27K 1100 Lm GU24 OmniLED
- GUL15A** - 15W/27K 1600 Lm GU24 OmniLED
- MBL15A** - 15./30K 1600 Lm OmniLED
- MB** - 150W Max Incand A (by others)

Finish

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded***
- RAL** - Specify Color #
- UPG** - Select Color from Luraline Palette
- Premium***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)

- DWG12** 12" Drop Wire Guard
- SSP 120** 4KV 120V MOV1 Surge Suppressor

NOTES: DWG Wire Guard may NOT be used in combination with CDL diffuser.
 DWG Wire Guard may NOT be used in combination with CDL diffuser.
 DWG Wire Guard may NOT be used in combination with CDL diffuser.
 DWG Wire Guard may NOT be used in combination with CDL diffuser.