



**Decorative CP12 STEMX** H: 13.50 W: 12.50 OAL: 29

**Description**

Prismatic reflector pendant with 12" stem and 40° swivel canopy

**Specifications**

<b>Housing</b>	Spun aluminum bullet with stamped steel canopy*
<b>Diffuser/Optics</b>	Lensed LED (no diffuser) for Dry locations only
<b>Light Source</b>	LED
<b>Max Watts</b>	16.41
<b>Electrical</b>	TL/HO - L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
<b>Mounting</b>	Mounts over 4" recessed outlet box.
<b>Certification</b>	Manufactured in accordance with U.L. standard 1598 - For dry locations only

**Ordering Guide:** Choose from each category, using designated code to specify.

CP12 STEMX				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

**Diffuser/Optics**

- Lensed LED (no diffuser)

**Light Source**

- TL3 HO** - 3.04W/40K 982 Lm, 0-10V dimmable
- TL3** - 3.11W/30K 603 Lm, 0-10V dimmable
- TL5 HO** - 4.59W/40K 1287 Lm, 120V dimmable
- TL5** - 4.7W/30K 909 Lm, 120V dimmable
- TL6** - 6.32W/30K 1208 Lm, 120V dimmable
- TL8 HO** - 7.75W/40K 1886 Lm, 120V dimmable
- TL8** - 7.96W/30K 1502 Lm, 120V dimmable
- TL9 HO** - 9.36W/40K 2179 Lm, 120V dimmable
- TL10** - 9.62W/30K 1790 Lm, 120V dimmable
- TL11** - 11.3W/30K 2075 Lm, 120V dimmable
- TL13 HO** - 12.62W/40K 2756 Lm, 120V dimmable
- TL13** - 12.99W/30K 2352 Lm, 120V dimmable
- TL16** - 16.41W/30K 2895 Lm, 120V dimmable

**Finish**

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded\***
- RAL** - Specify Color #
- UPG** - Select Color from Luraline Palette
- Premium\***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- \* Subject to Surcharge

**Extras (Order Separately)**

- 27K** Non-Stock item - consult factory for availability
- 35K** Neutral White
- DIM010** 4-wire 0-10V Dimming - 120-277V (STANDARD on TL19 & higher)
- DWG12** 12" Drop Wire Guard
- SSP** 10KV 120-277V Supplemental Surge Protection

NOTES:  
\*Driver is housed in extended aluminum canopy (not shown)