



RLM CS 16 CORD H: 10.38 W: 16.25

Description

12/' RLM pendant with 36" Black 18-3 cord. (White cord supplied with white fixtures)

Specifications

Housing Spun aluminum shade with stamped steel canopy

Diffuser/Optics Bare lamp (no diffuser) for Dry locations only

Light Source	GUL	MBL	Medium Base
Max Watts	15	18	150

Electrical

- MB** - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.
- MBL** - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures.
- GUL** - Includes GU24 base 120V HPF Triac dimmable 25,000 Hr OmniLED A lamp with integrated driver.

Mounting Mounts over 4" recessed outlet box.

Certification Manufactured in accordance with U.L. standard 1598 - For dry locations only



Ordering Guide: Choose from each category, using designated code to specify.

CS 16 CORD					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

Diffuser/Optics

Bare-lamp (no diffuser)

Light Source

MB25 A - 25W MAX. MED base (A19 lamp by others)
MBL6A - 5.5W/30K 470 Lm OmniLED
MBL9.8A - 9.8W/30K 800 Lm OmniLED
MBL10A JA8 - 10W/30K 800 Lm 90+ CRI OmniLED
MBL11A - 11W/30K 1100 Lm OmniLED
GUL11A - 11W/27K 1100 Lm GU24 OmniLED
MBL13A JA8 - 13W/30K 1100 Lm 90+ CRI OmniLED
GUL15A - 15W/27K 1600 Lm GU24 OmniLED
MBL15A - 15./30K 1600 Lm OmniLED
MBL18A JA8 - 18W/30K 1600 Lm 90+ CRI OmniLED
MB - 150W Max Incand A (by others)

Finish

Standard
BL - Black
DB - Dura-Bronze
WH - White
Upgraded*
RAL - Specify Color #
UPG - Select Color from Luraline Palette
Premium*
CCM - Custom Color
CIC - Inner Color
CTC - Clear Top Coat
 * Subject to Surcharge

Extras (Order Separately)

DWG16 16" Wire Guard
SSP 120 4KV 120V MOV1 Surge Suppressor

NOTES: DWG Wire Guard may NOT be used in combination with CDL diffuser.
 DWG Wire Guard may NOT be used in combination with CDL diffuser.