



**Legacy Product GWU 900** H: 15 W: 9

**Description**

MOQ may apply - please consult factory.  
Heavy-wall spun aluminum with cast fitter/canopy and extruded arm

**Specifications**

<b>Housing</b>	Heavy-wall spun aluminum with cast fitter/canopy and extruded arm		
<b>Diffuser/Optics</b>	<ul style="list-style-type: none"> <li>• Clear prismatic glass cylinder</li> <li>• Frosted glass cylinder</li> </ul>		
<b>Light Source</b>	GUL	MBL	Medium Base
<b>Max Watts</b>	11	13	100
<b>Electrical</b>	<p><b>MB</b> - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.  <b>MBL</b> - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures.  <b>GUL</b> - Includes GU24 base 120V HPF Triac dimmable 25,000 Hr OmniLED A lamp with integrated driver.</p>		
<b>Mounting</b>	Mounts over 4" recessed outlet box.		
<b>Certification</b>	Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations		

**Ordering Guide:** Choose from each category, using designated code to specify.

GWU 900					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

**Diffuser/Optics**

**CPR** - Clear prismatic glass  
**FR** - Frosted glass

**Light Source**

**GUL9.8A** - 9.8W/27K 800 Lm GU24 OmniLED  
**MBL11A** - 11W/30K 1100 Lm OmniLED  
**GUL11A** - 11W/27K 1100 Lm GU24 OmniLED  
**MBL13A JAB** - 13W/30K 1100 Lm 90+ CRI OmniLED  
**MB** - 100W Max Incand A (by others)

**Finish**

**Standard**  
**BL** - Black  
**DB** - Dura-Bronze  
**WH** - White  
**Upgraded\***  
**RAL** - Specify Color #  
**UPG** - Select Color from Luraline Palette  
**Premium\***  
**CCM** - Custom Color  
**CIC** - Inner Color  
**CTC** - Clear Top Coat  
 \* Subject to Surcharge

**Extras (Order Separately)**