



Helos HL301 CORD H: 11 W: 10 OAL: 47

Description

10" Disk Helos pendant with 36" Black 18-3 cord. (White cord supplied with white fixtures)

Specifications

Housing	Heavy-wall spun aluminum with cast fitter and stamped steel canopy	
Diffuser/Optics	<ul style="list-style-type: none"> • Clear tempered glass cylinder • Frosted Glass cylinder 	
Light Source	MBL	Medium Base
Max Watts	13	100
Electrical	MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures. MBL - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures.	
Mounting	Mounts over 4" recessed outlet box.	
Certification	Manufactured in accordance with U.L. standard 1598 - For dry locations only	



Ordering Guide: Choose from each category, using designated code to specify.

HL301 CORD					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

Diffuser/Optics

CL - Clear glass
FR - Frosted glass

Light Source

MB25 A - 25W MAX. MED base (A19 lamp by others)
MBL6A - 5.5W/30K 470 Lm OmniLED
MBL9.8A - 9.8W/30K 800 Lm OmniLED
MBL10A JA8 - 10W/30K 800 Lm 90+ CRI OmniLED
MBL13A JA8 - 13W/30K 1100 Lm 90+ CRI OmniLED
MB - 100W Max Incand A (by others)

Finish

Standard
BL - Black
DB - Dura-Bronze
WH - White
Upgraded*
RAL - Specify Color #
UPG - Select Color from Luraline Palette
Premium*
CCM - Custom Color
CIC - Inner Color
CTC - Clear Top Coat
 * Subject to Surcharge

Extras (Order Separately)

SSP 120 4KV 120V MOV1 Surge Suppressor