



**Helos HL301 P2** H: 19.25 W: 10 E: 37

**Description**

10" Disk, Double U-arm postlight (slips 3")

**Specifications**

<b>Housing</b>	Heavy-wall spun aluminum with cast fitter and extruded arm		
<b>Diffuser/Optics</b>	<ul style="list-style-type: none"> <li>• Clear prismatic glass cylinder</li> <li>• Clear tempered glass cylinder</li> <li>• Frosted Glass cylinder</li> </ul>		
<b>Light Source</b>	GUL	MBL	Medium Base
<b>Max Watts</b>	11 X 2	25 X 2	100 X 2
<b>Electrical</b>	<p><b>MB</b> - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.</p> <p><b>MBL</b> - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures.</p> <p><b>GUL</b> - Includes GU24 base 120V HPF Triac dimmable 25,000 Hr OmniLED A lamp with integrated driver.</p>		
<b>Mounting</b>	Slips 3" OD (PX Series) poles - order separately		
<b>Certification</b>	Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations		



**Ordering Guide:** Choose from each category, using designated code to specify.

HL301 P2					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

**Diffuser/Optics**

- CL** - Clear glass
- CPR** - Clear prismatic glass
- FR** - Frosted glass

**Light Source**

- 2MBL6A** - 11W/30K 940 Lm OmniLED
- 2GUL9.8A** - 19.6W/27K 1600 Lm GU24 OmniLED
- 2MBL9.8A** - 19.6W/30K 1600 Lm OmniLED
- 2MBL10A JAS** - 20W/30K 1600 Lm 90+ CRI OmniLED
- 2GUL11A** - 22W/27K 2200 Lm GU24 OmniLED
- 2MB25A** - 2x 25W MAX. MED base (lamp by others)
- MB** - Maximum 2x 100W A (by others)

**Finish**

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded\***
- RAL** - Specify Color #
- UPG** - Select Color from Luraline Palette
- Premium\***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- \* Subject to Surcharge

**Extras (Order Separately)**