



Helos HL301 STEM H: 10 W: 10 OAL: 23.50

Description

10" Disk pendant with 12" stem and 40° swivel canopy

Specifications

- Housing** Heavy-wall spun aluminum with cast fitter, extruded stem and stamped steel canopy
- Diffuser/Optics**
 - Clear tempered glass cylinder
 - Frosted Glass cylinder
- Light Source**

GUL	MBL	Medium Base
-----	-----	-------------
- Max Watts**

11	13	100
----	----	-----
- Electrical**
 - MB** - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.
 - MBL** - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures.
 - GUL** - Includes GU24 base 120V HPF Triac dimmable 25,000 Hr OmniLED A lamp with integrated driver.
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 - Suitable for damp locations



Ordering Guide: Choose from each category, using designated code to specify.

HL301 STEM					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

Diffuser/Optics

- CL - Clear glass
- FR - Frosted glass

Light Source

- MB25 A** - 25W MAX. MED base (A19 lamp by others)
- MBL6A** - 5.5W/30K 470 Lm OmniLED
- MBL9.8A** - 9.8W/30K 800 Lm OmniLED
- GUL9.8A** - 9.8W/27K 800 Lm GU24 OmniLED
- MBL10A JA8** - 10W/30K 800 Lm 90+ CRI OmniLED
- GUL11A** - 11W/27K 1100 Lm GU24 OmniLED
- MBL11A** - 11W/30K 1100 Lm OmniLED
- MBL13A JA8** - 13W/30K 1100 Lm 90+ CRI OmniLED
- MB** - 100W Max Incand A (by others)

Finish

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded***
- RAL** - Specify Color #
- UPG** - Select Color from Luraline Palette
- Premium***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)

- SSP 120** 4KV 120V MOV1 Surge Suppressor