



Helos HL333 H: 8.75 W: 10

Description

10" Disk, Helos surface-mounted

Specifications

Housing	Heavy wall spun aluminum with cast fitter	
Diffuser/Optics	<ul style="list-style-type: none"> • Clear prismatic glass cylinder • Clear tempered glass cylinder • Frosted Glass cylinder 	
Light Source	MBL	Medium Base
Max Watts	13	100
Electrical	MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures. MBL - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures.	
Mounting	Mounts over 4" recessed outlet box.	
Certification	Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations	

Ordering Guide: Choose from each category, using designated code to specify.

HL333					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

Diffuser/Optics

- CL - Clear glass
- CPR - Clear prismatic glass
- FR - Frosted glass

Light Source

- MBL6A - 5.5W/30K 470 Lm OmniLED
- MBL9.8A - 9.8W/30K 800 Lm OmniLED
- MBL10A JAB - 10W/30K 800 Lm 90+ CRI OmniLED
- MBL13A JAB - 13W/30K 1100 Lm 90+ CRI OmniLED
- MB - 100W Max Incand A (by others)

Finish

- Standard**
- BL - Black
- DB - Dura-Bronze
- WH - White
- Upgraded***
- RAL - Specify Color #
- UPG - Select Color from Luraline Palette
- Premium***
- CCM - Custom Color
- CIC - Inner Color
- CTC - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)