



Helos HL333XL H: 11.25 W: 18

Description

18" Disk, Helos surface-mounted

Specifications

Housing	Heavy wall spun aluminum with cast fitter		
Diffuser/Optics	<ul style="list-style-type: none"> • Clear prismatic glass cylinder • Clear tempered glass cylinder • Frosted Glass cylinder 		
Light Source	GUL	MBL	Medium Base
Max Watts	15	15	200
Electrical	<p>MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.</p> <p>MBL - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures.</p> <p>GUL - Includes GU24 base 120V HPF Triac dimmable 25,000 Hr OmniLED A lamp with integrated driver.</p>		
Mounting	Mounts over 4" recessed outlet box.		
Certification	Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations		

Ordering Guide: Choose from each category, using designated code to specify.

HL333XL					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

Diffuser/Optics

- CL - Clear glass
- CPR - Clear prismatic glass
- FR - Frosted glass

Light Source

- MB25 A - 25W MAX. MED base (A19 lamp by others)
- MBL11A - 11W/30K 1100 Lm OmniLED
- GUL11A - 11W/27K 1100 Lm GU24 OmniLED
- GUL15A - 15W/27K 1600 Lm GU24 OmniLED
- MBL15A - 15./30K 1600 Lm OmniLED
- MB - Maximum 200W A (by others)

Finish

- Standard**
- BL - Black
- DB - Dura-Bronze
- WH - White
- Upgraded***
- RAL - Specify Color #
- UPG - Select Color from Luraline Palette
- Premium***
- CCM - Custom Color
- CIC - Inner Color
- CTC - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)