



Cutoff/Downlight HLD302 CORDX H: 9.50 W: 14 OAL: 47

Description

Helos Cutoff pendant with 36" Black 18-3 cord. (White cord supplied with white fixtures)

Specifications

- Housing** Spun aluminum with stamped steel canopy*:
- Diffuser** Bare lamp (no diffuser)
- Light Source** LED
- Max Watts** 13
- Electrical** COB - Includes >50,000 Hr. TurboLED with 120-277V HPF (LE-TE @120V) constant current driver dimmable.
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 -

Ordering Information Choose one from each category, filling in the guide using designated code.

Guide	HLD302 CORDX				
	MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

- | | | | |
|--|---|---|---|
| <p>Diffuser</p> <ul style="list-style-type: none"> - Bare-lamp (no diffuser) | <p>Light Source</p> <ul style="list-style-type: none"> TL11.5 COB - 11.5W/30K 1947 Lm TurboLED TL13 COB - 13W/30K 2209 Lm TurboLED | <p>Finish</p> <ul style="list-style-type: none"> Standard BL - Black DB - Dura-Bronze WH - White Upgraded* RAL - Specify Color # UPG - Select Color from Luraline Palette Premium* CCM - Custom Color CIC - Inner Color CTC - Clear Top Coat * Subject to Surcharge | <p>Extras (Order Separately)</p> <ul style="list-style-type: none"> 27K Warm White 90+ CRI TurboLED DIM120 120V 2-wire dimming (LMH models only) |
|--|---|---|---|

NOTES:
*Ballast/Driver is housed in extended aluminum canopy (not shown)