



Helos HLD302 CORDX H: 9.50 W: 14 OAL: 47

Description

Helos Cutoff pendant with 36" Black 18-3 cord. (White cord supplied with white fixtures)

Specifications

| | |
|------------------------|---|
| Housing | Spun aluminum with stamped steel canopy*: |
| Diffuser/Optics | Lensed LED (no diffuser) for Dry locations only |
| Light Source | LED |
| Max Watts | 16.4 |
| Electrical | COB/HO- L90 >55,000 Hr. TurboLED with 120-277V HPF Constant Current driver, LE-TE dimmable @120V or optional 0-10V dimming. |
| Mounting | Mounts over 4" recessed outlet box. |
| Certification | Manufactured in accordance with U.L. standard 1598 - |

Ordering Guide: Choose from each category, using designated code to specify.

| | | | | |
|--------------|----------|--------------|--------|--------|
| HLD302 CORDX | | | | |
| MODEL | DIFFUSER | LIGHT SOURCE | FINISH | EXTRAS |

Diffuser/Optics

- Lensed LED (no diffuser)

Light Source

- TL3.0 HO - 3.04W/40K 919 Lm TurboLED
- TL3 COB - 3.1W/30K 566 Lm TurboLED
- TL4.6 HO - 4.6W/40K 1204 Lm TurboLED
- TL4.7 COB - 4.7W/30K 854 Lm TurboLED
- TL6.2 HO - 6.18W/40K 1486 Lm TurboLED
- TL6.5 COB - 6.3W/30K 1135 Lm TurboLED
- TL7.8 HO - 7.77W/40K 1764 Lm TurboLED
- TL9.4 HO - 9.38W/40K 2039 Lm TurboLED
- TL9.6 COB - 9.6W/30K 1682 Lm TurboLED
- TL11.0 HO - 11.01W/40K 2310 Lm TurboLED
- TL11.5 COB - 11.3W/30K 1947 Lm TurboLED
- TL12.7 HO - 12.66W/40K 2578 Lm TurboLED
- TL13 COB - 13W/30K 2209 Lm TurboLED
- TL14.3 HO - 14.31W/40K 2843 Lm TurboLED
- TL15 COB - 14.7W/30K 2465 Lm TurboLED
- TL16.0 HO - 15.98W/40K 3105 Lm TurboLED
- TL16.5 COB - 16.45W/30K 2718 Lm TurboLED

Finish

- Standard**
- BL - Black
- DB - Dura-Bronze
- WH - White
- Upgraded***
- RAL - Specify Color #
- UPG - Select Color from Luraline Palette
- Premium***
- CCM - Custom Color
- CTC - Inner Color
- CTC - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)

27K Non-Stock item - consult factory for availability

NOTES:
*Driver is housed in extended aluminum canopy (not shown)