



Cutoff/Downlight HLD302 CORDX H: 9.50 W: 14 OAL: 47

Description

Helos Cutoff pendant with 36" Black 18-3 cord. (White cord supplied with white fixtures)

Specifications

- Housing** Spun aluminum with stamped steel canopy*:
- Diffuser** Bare lamp (no diffuser)
- Light Source** LED
- Max Watts** 13
- Electrical** LMH - Includes 120V HPF Triac dimmable 50,000 Hr. LED module with constant current driver.
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 -
- Applications** Commercial (indoor), Hospitals, Hotel/Motel & Hospitality, Industrial, Residential (indoor), Restaurants

Ordering Information Choose one from each category, filling in the guide using designated code.

| | | | | | |
|-------|--------------|----------|--------------|--------|--------|
| Guide | HLD302 CORDX | | | | |
| | MODEL | DIFFUSER | LIGHT SOURCE | FINISH | EXTRAS |

- | | | | |
|--|---|---|---|
| <p>Diffuser</p> <ul style="list-style-type: none"> - Bare-lamp (no diffuser) | <p>Light Source</p> <ul style="list-style-type: none"> TL11.5 COB - 11.5W/30K 1947 Lm TurboLED TL13 COB - 13W/30K 2209 Lm TurboLED | <p>Finish</p> <p>Standard</p> <ul style="list-style-type: none"> BL - Black DB - Dura-Bronze WH - White <p>Upgraded*</p> <ul style="list-style-type: none"> RAL - Specify Color # UPG - Select Color from Luraline Palette <p>Premium*</p> <ul style="list-style-type: none"> CCM - Custom Color CIC - Inner Color CTC - Clear Top Coat <p>* Subject to Surcharge</p> | <p>Extras (Order Separately)</p> <ul style="list-style-type: none"> 27K Warm White 90+ CRI TurboLED DIM120 120V 2-wire dimming (LMH models only) |
|--|---|---|---|

NOTES:
*Ballast/Driver is housed in extended aluminum canopy (not shown)