



Helos HLD302 STEMX H: 9.50 W: 14 OAL: 23.50

Description

Specifications

- Housing** Spun aluminum bullet/shade, 12" (std), 11/16" Dia stem, 40° swivel canopy - steel ball-aligner canopy*
- Diffuser/Optics**
 - Lensed LED (no diffuser) for Dry locations only
 - TurboLED Extra wide beam silicone optic
 - TurboLED wide beam silicone optic
- Light Source** LED
- Max Watts** 16.4
- Electrical** COB/HO- L90 >55,000 Hr. TurboLED with 120-277V HPF Constant Current driver, LE-TE dimmable @120V or optional 0-10V dimming.
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 - For dry locations only

Ordering Guide: Choose from each category, using designated code to specify.

HLD302 STEMX

MODEL DIFFUSER LIGHT SOURCE FINISH EXTRAS

Diffuser / Optics

- Lensed LED (no diffuser)
- LOW** - Wide beam optic
- LOX** - Extra wide beam optic

Light Source

- TL3.0 HO** - 3.04W/40K 919 Lm TurboLED
- TL3 COB** - 3.1W/30K 566 Lm TurboLED
- TL4.6 HO** - 4.6W/40K 1204 Lm TurboLED
- TL4.7 COB** - 4.7W/30K 854 Lm TurboLED
- TL6.2 HO** - 6.18W/40K 1486 Lm TurboLED
- TL6.5 COB** - 6.3W/30K 1135 Lm TurboLED
- TL7.8 HO** - 7.77W/40K 1764 Lm TurboLED
- TL8 COB** - 8W/30K 1411 Lm TurboLED
- TL9.4 HO** - 9.38W/40K 2039 Lm TurboLED
- TL9.6 COB** - 9.6W/30K 1682 Lm TurboLED
- TL11.0 HO** - 11.01W/40K 2310 Lm TurboLED
- TL11.5 COB** - 11.3W/30K 1947 Lm TurboLED
- TL12.7 HO** - 12.66W/40K 2578 Lm TurboLED
- TL13 COB** - 13W/30K 2209 Lm TurboLED
- TL14.3 HO** - 14.31W/40K 2843 Lm TurboLED
- TL15 COB** - 14.7W/30K 2465 Lm TurboLED
- TL16.0 HO** - 15.98W/40K 3105 Lm TurboLED
- TL16.5 COB** - 16.45W/30K 2718 Lm TurboLED

Finish

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded***
- RAL** - Specify Color #
- UPG** - Select Color from Luraline Palette
- Premium***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)

- 22K** Candlelight 90+ CRI (MOQ item - NCNR)
- 27K** Non-Stock item - consult factory for availability
- 35K**
- 50K** Daylight (MOQ item - NCNR)
- DIM010** 4-wire 0-10V Dimming - 120-277V
- SSP** 10KV 120-277V Supplemental Surge Protection

NOTES: *Driver is housed in extended aluminum canopy (not shown)