



Cutoff/Downlight HLD302 STEMX H: 9.50 W: 14 OAL: 23.50

Description

Specifications

- Housing** Spun aluminum bullet/shade, 12" (std), 11/16" Dia stem, 40° swivel canopy - steel ball-aligner canopy*
- Diffuser/Optics** Bare Lamp (open aperture)
- Light Source** LED
- Max Watts** 13
- Electrical** COB - Includes >50,000 Hr. TurboLED with 120-277V HPF (LE-TE @120V) constant current driver dimmable.
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 -

Ordering Information Choose one from each category, filling in the guide using designated code.

Guide	HLD302 STEMX				
	MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

- Bare-lamp (open aperture)

Light Source

TL11 COB - 11.3W/30K 1947 Lm TurboLED
TL13 COB - 13W/30K 2209 Lm TurboLED

Finish

Standard
BL - Black
DB - Dura-Bronze
WH - White
Upgraded*
RAL - Specify Color #
UPG - Select Color from
Luraline Palette
Premium*
CCM - Custom Color
CIC - Inner Color
CTC - Clear Top Coat
 * Subject to Surcharge

Extras (Order Separately)

27K Warm White 90+ CRI TurboLED
DIM120 120V 2-wire dimming (LMH models only)

NOTES:
 *Ballast/Driver is housed in extended aluminum canopy (not shown)