



Cutoff/Downlight HLD302 STEMX H: 9.50 W: 14 OAL: 23.50

Description

Specifications

- Housing** Spun aluminum bullet/shade, 12" (std), 11/16" Dia stem, 40° swivel canopy - steel ball-aligner canopy*
- Diffuser** Bare Lamp (open aperture)
- Light Source** LED
- Max Watts** 13
- Electrical** LMH - Includes 120V HPF Triac dimmable 50,000 Hr. LED module with constant current driver.
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 - Suitable for damp or dry locations

Ordering Information Choose one from each category, filling in the guide using designated code.

Guide	HLD302 STEMX				
	MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

- | | | | |
|--|---|---|---|
| <p>Diffuser</p> <ul style="list-style-type: none"> - Bare-lamp (open aperture) | <p>Light Source</p> <ul style="list-style-type: none"> TL11.5 COB - 11.5W/30K 1947 Lm TurboLED TL13 COB - 13W/30K 2209 Lm TurboLED | <p>Finish</p> <ul style="list-style-type: none"> Standard BL - Black DB - Dura-Bronze WH - White Upgraded* RAL - Specify Color # UPG - Select Color from Luraline Palette Premium* CCM - Custom Color CIC - Inner Color CTC - Clear Top Coat * Subject to Surcharge | <p>Extras (Order Separately)</p> <ul style="list-style-type: none"> 27K Warm White 90+ CRI TurboLED DIM120 120V 2-wire dimming (LMH models only) |
|--|---|---|---|

NOTES:
*Ballast/Driver is housed in extended aluminum canopy (not shown)