



Cutoff/downlight HLD302XL PR H: 30.50 W: 22 E: 34.50

Description

22" Tapered shade, U-arm postlight (slips 4") Down light only!

Specifications

Housing Spun aluminum shade with extruded arm and cast fitter

Diffuser Lensed LED module (no diffuser)
(for use in Dry or Damp locations)

Electrical LMH - Includes 120V HPF Triac dimmable 50,000 Hr. LED module with constant current driver.

Mounting Slips 4" OD (PR Series) poles - order separately

Certification Manufactured in accordance with U.L. standard 1598 -

Applications Commercial (outdoor), Hospitals, Hotel/Motel & Hospitality, Industrial, Landscape, Parking/Garages, Restaurants, Site Lighting

Ordering Information Choose one from each category, filling in the guide using designated code.

Guide	HLD302XL PR				
	MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser
LED module (no diffuser)

Light Source

Finish
Standard
BL - Black
DB - Dura-Bronze
WH - White
Upgraded*
RAL - Specify Color #
UPG - Select Color from
Luraline Palette
Premium*
CCM - Custom Color
CIC - Inner Color
CTC - Clear Top Coat
* Subject to Surcharge

Extras (Order Separately)