



**Cutoff/Downlight HLD302XL STEMX H: 15.75 W: 22 OAL: 31.25**

**Description**

**Specifications**

- Housing** Spun aluminum with extruded stem and stamped steel canopy\*
- Diffuser/Optics** Bare lamp (no diffuser)
- Light Source** LED
- Max Watts** 30.6
- Electrical Mounting** COB - Includes >50,000 Hr. TurboLED with 120-277V HPF (LE-TE @120V) constant current driver dimmable. Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 -



**Ordering Information** Choose one from each category, filling in the guide using designated code.

Guide	HLD302XL STEMX				
	MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

**Diffuser/Optics**

- Bare-lamp (no diffuser)

**Light Source**

**TL27 COB** - 27W/30K 4158 Lm TurboLED  
**TL31 COB** - 30.6W/30K 4613 Lm TurboLED

**Finish**

**Standard**  
**BL** - Black  
**DB** - Dura-Bronze  
**WH** - White  
**Upgraded\***  
**RAL** - Specify Color #  
**UPG** - Select Color from Luraline Palette  
**Premium\***  
**CCM** - Custom Color  
**CIC** - Inner Color  
**CTC** - Clear Top Coat  
 \* Subject to Surcharge

**Extras (Order Separately)**

**27K** Warm White 90+ CRI TurboLED

NOTES: \*Ballast/Driver is housed in extended aluminum canopy (not shown)