



Cutoff/Downlight HLD302XL STEMX H: 15.75 W: 22 OAL: 31.25

Description

Specifications

- Housing** Spun aluminum with extruded stem and stamped steel canopy*
- Diffuser** Bare lamp (no diffuser)
- Light Source** LED
- Max Watts** 30
- Electrical** LMH - Includes 120V HPF Triac dimmable 50,000 Hr. LED module with constant current driver.
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 - Suitable for damp or dry locations

Ordering Information Choose one from each category, filling in the guide using designated code.

Guide	HLD302XL STEMX				
	MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

- | | | | |
|--|---|---|--|
| <p>Diffuser</p> <ul style="list-style-type: none"> - Bare-lamp (no diffuser) | <p>Light Source</p> <ul style="list-style-type: none"> TL27 COB - 27W/30K 4158 Lm TurboLED TL31 COB - 31W/30K 4613 Lm TurboLED | <p>Finish</p> <ul style="list-style-type: none"> Standard BL - Black DB - Dura-Bronze WH - White Upgraded* RAL - Specify Color # UPG - Select Color from Luraline Palette Premium* CCM - Custom Color CIC - Inner Color CTC - Clear Top Coat * Subject to Surcharge | <p>Extras (Order Separately)</p> <ul style="list-style-type: none"> 27K Warm White 90+ CRI TurboLED |
|--|---|---|--|

NOTES:
*Ballast/Driver is housed in extended aluminum canopy (not shown)