



Helos HLD302XL STEMX H: 15.75 W: 22 OAL: 31.25

Description

Specifications

- Housing** Spun aluminum with extruded stem and stamped steel canopy*
- Diffuser/Optics**
 - Lensed LED (no diffuser) for Dry locations only
 - TurboLED Extra wide beam silicone optic
 - TurboLED wide beam silicone optic
- Light Source** LED
- Max Watts** 36.1
- Electrical** COB/HO- L90 >55,000 Hr. TurboLED with 120-277V HPF Constant Current driver, LE-TE dimmable @120V or optional 0-10V dimming.
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 -



Ordering Guide: Choose from each category, using designated code to specify.

HLD302XL STEMX				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

- Lensed LED (no diffuser)
- LOW** - Wide beam optic
- LOX** - Extra wide beam optic

Light Source

- TL11.0 HO** - 11.01W/40K 2310 Lm TurboLED
- TL19.4 HO** - 19.35W/40K 3620 Lm TurboLED
- TL20 COB** - 19.9W/30K 3212 Lm TurboLED
- TL22.8 HO** - 22.77W/40K 4125 Lm TurboLED
- TL23.5 COB** - 23.4W/30K 3691 Lm TurboLED
- TL26.2 HO** - 26.22W/40K 4618 Lm TurboLED
- TL27 COB** - 27W/30K 4158 Lm TurboLED
- TL29.7 HO** - 29.72W/40K 5105 Lm TurboLED
- TL31 COB** - 30.6W/30K 4613 Lm TurboLED
- TL35.0 HO** - 35.04W/40K 5811 Lm TurboLED
- TL36 COB** - 36.1W/30K 5277 Lm TurboLED

Finish

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded***
- RAL** - Specify Color #
- UPG** - Select Color from Luraline Palette
- Premium***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)

- 22K** Candlelight 90+ CRI (MOQ item - NCNR)
- 27K** Non-Stock item - consult factory for availability
- 35K** Non-Stock item - consult factory for availability
- 50K** Daylight (MOQ item - NCNR)
- DIM010** 4-wire 0-10V Dimming - 120-277V
- SSP** 10KV 120-277V Supplemental Surge Protection

NOTES: *Driver is housed in extended aluminum canopy (not shown)