



Cutoff/Downlight HLD302XL WM H: 15.50 W: 22 E: 28 MC: 4.50

Description

22" Tapered shade downlight, straight arm

Specifications

- Housing** Spun aluminum shade with extruded arm and cast canopy*
- Diffuser/Optics**
 - Bare lamp (no diffuser)
 - Extra Wide Beam TurboLED Optic
 - Omni-directional TurboLED Optic
 - Wide Beam TurboLED Optic
- Light Source** LED
- Max Watts** 30.6
- Electrical Mounting** COB - Includes >50,000 Hr. TurboLED with 120-277V HPF (LE-TE @120V) constant current driver dimmable. Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 -



Ordering Information Choose one from each category, filling in the guide using designated code.

Guide	HLD302XL WM				
	MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

- Bare-lamp (no diffuser)
- LOW** - Stella Wide Beam Silicone LED Optic
- LOX** - Stella Extra Wide Beam Silicone LED Optic
- LOZ** - Zorya Omni-directional LED Optic

Light Source

- TL27 COB** - 27W/30K 4158 Lm TurboLED
- TL31 COB** - 30.6W/30K 4613 Lm TurboLED

Finish

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded***
- RAL** - Specify Color #
- UPG** - Select Color from Luraline Palette
- Premium***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)

- 27K** Warm White 90+ CRI TurboLED
- 35K** Neutral CW TurboLED
- 40K** Cool White TurboLED