



Cutoff/Downlight HLD302XL WM H: 15.50 W: 22 E: 28 MC: 4.50

Description

22" Tapered shade downlight, straight arm

Specifications

- Housing** Spun aluminum shade with extruded arm and cast canopy*
- Diffuser** Bare lamp (no diffuser)
- Light Source** LED
- Max Watts** 30
- Electrical** LMH - Includes 120V HPF Triac dimmable 50,000 Hr. LED module with constant current driver.
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 -

Ordering Information Choose one from each category, filling in the guide using designated code.

Guide	HLD302XL WM				
	MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser
- Bare-lamp (no diffuser)

Light Source
TL27 COB - 27W/30K 4158 Lm TurboLED
TL31 COB - 31W/30K 4613 Lm TurboLED

Finish
Standard
BL - Black
DB - Dura-Bronze
WH - White
Upgraded*
RAL - Specify Color #
UPG - Select Color from [Luraline Palette](#)
Premium*
CCM - Custom Color
CIC - Inner Color
CTC - Clear Top Coat
 * Subject to Surcharge

Extras (Order Separately)
27K Warm White 90+ CRI TurboLED
35K Neutral CW TurboLED
40K Cool White TurboLED