



**Cutoff/Downlight HLD314 CORDX** H: 8.25 W: 14 OAL: 46.75

**Description**

Helos Cutoff pendant with 36" Black 18-3 cord. (White cord supplied with white fixtures)

**Specifications**

- Housing** Spun aluminum with stamped steel canopy\*:
- Diffuser/Optics** Lensed LED module (no diffuser)  
(for use in Dry or Damp locations)
- Light Source** LED
- Max Watts** 13
- Electrical** LMH - Includes 120V HPF Triac dimmable 50,000 Hr. LED module with constant current driver.
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 -

**Ordering Information** Choose one from each category, filling in the guide using designated code.

Guide	HLD314 CORDX				
	MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

**Diffuser/Optics**

LED module (no diffuser)

**Light Source**

**TL11 COB** - 11.3W/30K 1947 Lm TurboLED  
**TL13 COB** - 13W/30K 2209 Lm TurboLED

**Finish**

**Standard**  
**BL** - Black  
**DB** - Dura-Bronze  
**WH** - White  
**Upgraded\***  
**RAL** - Specify Color #  
**UPG** - Select Color from  
Luraline Palette  
**Premium\***  
**CCM** - Custom Color  
**CIC** - Inner Color  
**CTC** - Clear Top Coat  
\* Subject to Surcharge

**Extras (Order Separately)**

**27K** Warm White 90+ CRI TurboLED  
**DIM120** 120V 2-wire dimming (LMH models only)

NOTES: \*Ballast/Driver is housed in extended aluminum canopy (not shown in photo)