



Helos HLD314 CORDX H: 8.25 W: 14 OAL: 46.75

Description

Helos Cutoff pendant with 36" Black 18-3 cord. (White cord supplied with white fixtures)

Specifications

Housing	Spun aluminum with stamped steel canopy*:
Diffuser/Optics	Lensed LED (no diffuser) for Dry locations only
Light Source	LED
Max Watts	16.4
Mounting	Mounts over 4" recessed outlet box.
Certification	Manufactured in accordance with U.L. standard 1598 - For dry locations only

Ordering Guide: Choose from each category, using designated code to specify.

<u>HLD314 CORDX</u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

- Lensed LED (no diffuser)

Light Source

- TL3.0 HO** - 3.04W/40K 919 Lm TurboLED
- TL3 COB** - 3.1W/30K 566 Lm TurboLED
- TL6.2 HO** - 6.18W/40K 1486 Lm TurboLED
- TL7.8 HO** - 7.77W/40K 1764 Lm TurboLED
- TL8 COB** - 8W/30K 1411 Lm TurboLED
- TL9.4 HO** - 9.38W/40K 2039 Lm TurboLED
- TL11.0 HO** - 11.01W/40K 2310 Lm TurboLED
- TL11.5 COB** - 11.3W/30K 1947 Lm TurboLED
- TL12.7 HO** - 12.66W/40K 2578 Lm TurboLED
- TL13 COB** - 13W/30K 2209 Lm TurboLED
- TL14.3 HO** - 14.31W/40K 2843 Lm TurboLED
- TL15 COB** - 14.7W/30K 2465 Lm TurboLED
- TL16.0 HO** - 15.98W/40K 3105 Lm TurboLED
- TL16.5 COB** - 16.45W/30K 2718 Lm TurboLED

Finish

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded***
- RAL** - Specify Color #
- UPG** - Select Color from Luraline Palette
- Premium***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)

- 22K** Candlelight 90+ CRI (MOQ item - NCNR)
- 27K** Non-Stock item - consult factory for availability
- 35K** Non-Stock item - consult factory for availability
- 50K** Daylight (MOQ item - NCNR)
- DIM010** 4-wire 0-10V Dimming - 120-277V
- SSP** 10KV 120-277V Supplemental Surge Protection

NOTES:
*Driver is housed in extended aluminum canopy (not shown in photo)