



**Cutoff/Downlight HLD314 CORDX H: 8.25 W: 14 OAL: 46.75**

**Description**

Helos Cutoff pendant with 36" Black 18-3 cord. (White cord supplied with white fixtures)

**Specifications**

- Housing** Spun aluminum with stamped steel canopy\*
- Diffuser** Lensed LED module (no diffuser)  
Â (for use in Dry or Damp locations)
- Light Source** LED
- Max Watts** 13
- Electrical** LMH - Includes 120V HPF Triac dimmable 50,000 Hr. LED module with constant current driver.
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 -

**Ordering Information** Choose one from each category, filling in the guide using designated code.

Guide	HLD314 CORDX				
	MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

- |  |  |   |  |
|--|--|---|--|
| <p><b>Diffuser</b></p> <p>LED module (no diffuser)</p> | <p><b>Light Source</b></p> <p><b>TL11.5 COB</b> - 11.5W/30K 1947 Lm TurboLED<br/> <b>TL13 COB</b> - 13W/30K 2209 Lm TurboLED</p> | <p><b>Finish</b></p> <p><b>Standard</b><br/> <b>BL</b> - Black<br/> <b>DB</b> - Dura-Bronze<br/> <b>WH</b> - White<br/> <b>Upgraded*</b><br/> <b>RAL</b> - <u>Specify Color #</u><br/> <b>UPG</b> - Select Color from<br/> <u>Luraline Palette</u><br/> <b>Premium*</b><br/> <b>CCM</b> - Custom Color<br/> <b>CIC</b> - Inner Color<br/> <b>CTC</b> - Clear Top Coat<br/> * Subject to Surcharge</p> | <p><b>Extras (Order Separately)</b></p> <p><b>27K</b> Warm White 90+ CRI TurboLED<br/> <b>DIM120</b> 120V 2-wire dimming (LMH models only)</p> |
|--|--|---|--|

NOTES: \*Ballast/Driver is housed in extended aluminum canopy (not shown in photo)