



Cutoff/Downlight HLD318 CORDX H: 9.75 W: 18 OAL: 48.25

Description

Helos Cutoff pendant with 36" Black 18-3 cord. (White cord supplied with white fixtures)

Specifications

- Housing** Spun aluminum with stamped steel canopy*
- Diffuser** Lensed LED module (no diffuser)
(for use in Dry or Damp locations)
- Light Source** LED
- Max Watts** 13
- Electrical** COB - Includes >50,000 Hr. TurboLED with 120-277V HPF (LE-TE @120V) constant current driver dimmable.
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 -

Ordering Information Choose one from each category, filling in the guide using designated code.

| | | | | | |
|-------|--------------|----------|--------------|--------|--------|
| Guide | HLD318 CORDX | | | | |
| | MODEL | DIFFUSER | LIGHT SOURCE | FINISH | EXTRAS |

- | | | | |
|--|--|--|---|
| <p>Diffuser</p> <p>LED module (no diffuser)</p> | <p>Light Source</p> <p>TL11.5 COB - 11.5W/30K 1947 Lm TurboLED TL13 COB - 13W/30K 2209 Lm TurboLED</p> | <p>Finish</p> <p>Standard BL - Black DB - Dura-Bronze WH - White Upgraded* RAL - <u>Specify Color #</u> UPG - Select Color from <u>Luraline Palette</u> Premium* CCM - Custom Color CIC - <u>Inner Color</u> CTC - Clear Top Coat * Subject to Surcharge</p> | <p>Extras (Order Separately)</p> <p>27K Warm White 90+ CRI TurboLED</p> |
|--|--|--|---|

NOTES: *Ballast/Driver is housed in extended aluminum canopy (not shown in photo)