



Cutoff/Downlight HLD318 CORDX H: 9.75 W: 18 OAL: 48.25

Description

Helos Cutoff pendant with 36" Black 18-3 cord. (White cord supplied with white fixtures)

Specifications

Housing	Spun aluminum with stamped steel canopy*
Diffuser/Optics	Lensed LED module (no diffuser) (for use in Dry or Damp locations)
Light Source	LED
Max Watts	13
Electrical	COB - Includes >50,000 Hr. TurboLED with 120-277V HPF (LE-TE @120V) constant current driver dimmable.
Mounting	Mounts over 4" recessed outlet box.
Certification	Manufactured in accordance with U.L. standard 1598 -

Ordering Information Choose one from each category, filling in the guide using designated code.

Guide	<u>HLD318 CORDX</u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>
	MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

LED module (no diffuser)

Light Source

TL11 COB - 11.3W/30K 1947 Lm TurboLED
TL13 COB - 13W/30K 2209 Lm TurboLED

Finish

Standard
BL - Black
DB - Dura-Bronze
WH - White
Upgraded*
RAL - Specify Color #
UPG - Select Color from Luraline Palette
Premium*
CCM - Custom Color
CIC - Inner Color
CTC - Clear Top Coat
* Subject to Surcharge

Extras (Order Separately)

27K Warm White 90+ CRI TurboLED

NOTES: *Ballast/Driver is housed in extended aluminum canopy (not shown in photo)