



Cutoff/Downlight HLD318 CORDX H: 9.75 W: 18 OAL: 48.25

Description

Helos Cutoff pendant with 36" Black 18-3 cord. (White cord supplied with white fixtures)

Specifications

- Housing** Spun aluminum with stamped steel canopy*
- Diffuser** Lensed LED module (no diffuser)
(for use in Dry or Damp locations)
- Light Source** LED
- Max Watts** 13
- Electrical** LMH - Includes 120V HPF Triac dimmable 50,000 Hr. LED module with constant current driver.
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 -

Ordering Information Choose one from each category, filling in the guide using designated code.

Guide	HLD318 CORDX				
	MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

- | | | | |
|--|--|--|---|
| <p>Diffuser</p> <p>LED module (no diffuser)</p> | <p>Light Source</p> <p>TL11.5 COB - 11.5W/30K 1947 Lm TurboLED
 TL13 COB - 13W/30K 2209 Lm TurboLED</p> | <p>Finish</p> <p>Standard
 BL - Black
 DB - Dura-Bronze
 WH - White
 Upgraded*
 RAL - Specify Color #
 UPG - Select Color from Luraline Palette
 Premium*
 CCM - Custom Color
 CIC - Inner Color
 CTC - Clear Top Coat
 * Subject to Surcharge</p> | <p>Extras (Order Separately)</p> <p>27K Warm White 90+ CRI TurboLED</p> |
|--|--|--|---|

NOTES: *Ballast/Driver is housed in extended aluminum canopy (not shown in photo)