



**Helos HLD318 STEMX** H: 9.75 W: 18

**Description**

**Specifications**

- Housing** Spun aluminum with extruded stem and stamped steel canopy\*
- Diffuser/Optics**
  - Lensed LED (no diffuser) for Dry locations only
  - TurboLED Extra wide beam silicone optic
  - TurboLED wide beam silicone optic
- Light Source** LED
- Max Watts** 11.3
- Electrical** COB/HO- L90 >55,000 Hr. TurboLED with 120-277V HPF Constant Current driver, LE-TE dimmable @120V or optional 0-10V dimming.
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 -

**Ordering Guide:** Choose from each category, using designated code to specify.



**Diffuser/Optics**

- Lensed LED (no diffuser)
- LOW** - Wide beam optic
- LOX** - Extra wide beam optic

**Light Source**

- TL4.7 COB** - 4.7W/30K 854 Lm TurboLED
- TL11.5 COB** - 11.3W/30K 1947 Lm TurboLED

**Finish**

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded\***
- RAL** - Specify Color #
- UPG** - Select Color from Luraline Palette
- Premium\***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- \* Subject to Surcharge

**Extras (Order Separately)**

- 27K** Non-Stock item - consult factory for availability
- 35K**
- DIM010** 4-wire 0-10V Dimming - 120-277V
- SSP** 10KV 120-277V Supplemental Surge Protection