



Cutoff/Downlight HLD318 STEMX H: 9.75 W: 18 OAL: 25.25

Description

Specifications

- Housing** Spun aluminum with extruded stem and stamped steel canopy*
- Diffuser** Lensed LED module (no diffuser)
(for use in Dry or Damp locations)
- Light Source** LED
- Max Watts** 13
- Electrical** COB - Includes 50,000 Hr. TurboLED with 120-277V HPF (LE-TE dimmable @120V) constant current driver.
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 -

Ordering Information Choose one from each category, filling in the guide using designated code.

Guide	HLD318 STEMX				
	MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser
LED module (no diffuser)

Light Source
TL11.5 COB - 11.5W/30K 1947 Lm TurboLED
TL13 COB - 13W/30K 2209 Lm TurboLED

Finish
Standard
BL - Black
DB - Dura-Bronze
WH - White
Upgraded*
RAL - Specify Color #
UPG - Select Color from Luraline Palette
Premium*
CCM - Custom Color
CIC - Inner Color
CTC - Clear Top Coat
 * Subject to Surcharge

Extras (Order Separately)
27K Warm White 90+ CRI TurboLED