



**Cutoff/Downlight HLD318 STEMX** H: 9.75 W: 18 OAL: 25.25

**Description**

**Specifications**

- Housing** Spun aluminum with extruded stem and stamped steel canopy\*
- Diffuser/Optics** Lensed LED module (no diffuser)  
(for use in Dry or Damp locations)
- Light Source** LED
- Max Watts** 13
- Electrical** COB - Includes >50,000 Hr. TurboLED with 120-277V HPF (LE-TE @120V) constant current driver dimmable.
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 -

**Ordering Information** Choose one from each category, filling in the guide using designated code.

Guide HLD318 STEMX

MODEL                      DIFFUSER                      LIGHT SOURCE                      FINISH                      EXTRAS

**Diffuser/Optics**  
LED module (no diffuser)

**Light Source**  
**TL11 COB** - 11.3W/30K 1947 Lm TurboLED  
**TL13 COB** - 13W/30K 2209 Lm TurboLED

**Finish**  
**Standard**  
**BL** - Black  
**DB** - Dura-Bronze  
**WH** - White  
**Upgraded\***  
**RAL** - [Specify Color #](#)  
**UPG** - [Select Color from Luraline Palette](#)  
**Premium\***  
**CCM** - Custom Color  
**CIC** - Inner Color  
**CTC** - Clear Top Coat  
\* Subject to Surcharge

**Extras (Order Separately)**  
**27K** Warm White 90+ CRI TurboLED