



Cutoff/Downlight HLD318 STEMX H: 9.75 W: 18 OAL: 25.25

Description

Specifications

- Housing** Spun aluminum with extruded stem and stamped steel canopy*
- Diffuser/Optics** Lensed LED module (no diffuser)
(for use in Dry or Damp locations)
- Light Source** LED
- Max Watts** 13
- Electrical** COB - Includes >50,000 Hr. TurboLED with 120-277V HPF (LE-TE @120V) constant current driver dimmable.
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 -

Ordering Information Choose one from each category, filling in the guide using designated code.

Guide HLD318 STEMX

MODEL DIFFUSER LIGHT SOURCE FINISH EXTRAS

Diffuser/Optics
LED module (no diffuser)

Light Source
TL11 COB - 11.3W/30K 1947 Lm TurboLED
TL13 COB - 13W/30K 2209 Lm TurboLED

Finish
Standard
BL - Black
DB - Dura-Bronze
WH - White
Upgraded*
RAL - [Specify Color #](#)
UPG - [Select Color from Luraline Palette](#)
Premium*
CCM - Custom Color
CIC - Inner Color
CTC - Clear Top Coat
* Subject to Surcharge

Extras (Order Separately)
27K Warm White 90+ CRI TurboLED