



Cutoff/downlight HLD322 PR H: 28.25 W: 22 E: 34.50

Description

Specifications

- Housing** Spun aluminum shade with extruded arm and cast fitter
- Diffuser/Optics**
 - Lensed LED (no diffuser) for Dry locations only
 - TurboLED Extra wide beam silicone optic
 - TurboLED wide beam silicone optic
- Light Source** LED
- Max Watts** 36.1
- Electrical** COB - Includes >50,000 Hr. COB LED module with 120-277V HPF 0-10V dimmable constant current driver.
- Mounting** Slips 4" OD (PR Series) poles - order separately
- Certification** Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations

Ordering Guide: Choose from each category, using designated code to specify.



Diffuser/Optics

- Lensed LED (no diffuser)
- LOW** - Wide beam optic
- LOX** - Extra wide beam optic

Light Source

- TL20 COB** - 19.9W/30K 3212 Lm TurboLED
- TL22.8 HO** - 22.77W/40K 4125 Lm TurboLED
- TL23.5 COB** - 23.4W/30K 3691 Lm TurboLED
- TL26.2 HO** - 26.22W/40K 4618 Lm TurboLED
- TL27 COB** - 27W/30K 4158 Lm TurboLED
- TL29.7 HO** - 29.72W/40K 5105 Lm TurboLED
- TL31 COB** - 30.6W/30K 4613 Lm TurboLED
- TL35.0 HO** - 35.04W/40K 5811 Lm TurboLED
- TL36 COB** - 36.1W/30K 5277 Lm TurboLED

Finish

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded***
- RAL** - Specify Color #
- UPG** - Select Color from [Luraline Palette](#)
- Premium***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)