



**Cutoff/downlight** HLD322 PR H: 28.25 W: 22 E: 34.50

**Description**

**Specifications**

Housing	Spun aluminum shade with extruded arm and cast fitter
Diffuser	Lensed LED module (no diffuser) Â (for use in Dry or Damp locations)
Light Source	LED
Max Watts	20
Mounting	Slips 4" OD (PR Series) poles - order seperately
Certification	Manufactured in accordance with U.L. standard 1598 -

**Ordering Information** Choose one from each category, filling in the guide using designated code.

Guide HLD322 PR \_\_\_\_\_ | \_\_\_\_\_ | \_\_\_\_\_ | \_\_\_\_\_ | \_\_\_\_\_

MODEL DIFFUSER LIGHT SOURCE FINISH EXTRAS

<b>Diffuser</b> LED module (no diffuser)	<b>Light Source</b> TL13 COB/P - 13W/30K 2209 Lm TurboLED TL20 COB/P - 20W/30K 3212 Lm TurboLED	<b>Finish</b> <b>Standard</b> BL - Black DB - Dura-Bronze WH - White <b>Upgraded*</b> RAL - <u>Specify Color #</u> UPG - Select Color from <u>Luraline Palette</u> <b>Premium*</b> CCM - Custom Color CIC - <u>Inner Color</u> CTC - Clear Top Coat * Subject to Surcharge	<b>Extras (Order Separately)</b>
---------------------------------------------	-------------------------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	----------------------------------