



Cutoff/downlight HLD322 PR H: 28.25 W: 22 E: 34.50

Description

Specifications

Housing	Spun aluminum shade with extruded arm and cast fitter
Diffuser	Lensed LED module (no diffuser) (for use in Dry or Damp locations)
Light Source	LED
Max Watts	20
Mounting	Slips 4" OD (PR Series) poles - order seperately
Certification	Manufactured in accordance with U.L. standard 1598 -
Applications	Commercial (outdoor), Hospitals, Hotel/Motel & Hospitality, Industrial, Landscape, Parking/Garages, Restaurants, Site Lighting

Ordering Information Choose one from each category, filling in the guide using designated code.

Guide HLD322 PR

MODEL DIFFUSER LIGHT SOURCE FINISH EXTRAS

Diffuser LED module (no diffuser)	Light Source TL13 COB/P - 13W/30K 2209 Lm TurboLED TL20 COB/P - 20W/30K 3212 Lm TurboLED	Finish Standard BL - Black DB - Dura-Bronze WH - White Upgraded* RAL - Specify Color # UPG - Select Color from Luraline Palette Premium* CCM - Custom Color CIC - Inner Color CTC - Clear Top Coat * Subject to Surcharge	Extras (Order Separately)
---	---	--	----------------------------------