



**Cutoff/downlight** HLD322 PR H: 28.25 W: 22 E: 34.50

**Description**

**Specifications**

Housing	Spun aluminum shade with extruded arm and cast fitter
Diffuser/Optics	Lensed LED module (no diffuser) (for use in Dry or Damp locations)
Light Source	LED
Max Watts	19.9
Mounting	Slips 4" OD (PR Series) poles - order separately
Certification	Manufactured in accordance with U.L. standard 1598 -

**Ordering Information** Choose one from each category, filling in the guide using designated code.

Guide	HLD322 PR				
	MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

**Diffuser/Optics**

LED module (no diffuser)

**Light Source**

**TL13 COB/P** - 13W/30K 2209 Lm TurboLED  
**TL20 COB/P** - 19.9W/30K 3212 Lm TurboLED

**Finish**

**Standard**  
**BL** - Black  
**DB** - Dura-Bronze  
**WH** - White  
**Upgraded\***  
**RAL** - Specify Color #  
**UPG** - Select Color from Luraline Palette  
**Premium\***  
**CCM** - Custom Color  
**CIC** - Inner Color  
**CTC** - Clear Top Coat  
 \* Subject to Surcharge

**Extras (Order Separately)**