



**Helos HLD322 STEMX** H: 13.25 W: 22 OAL: 28.75

**Description**

Helos Cutoff pendant with 12" stem and 40° swivel canopy

**Specifications**

<p><b>Housing</b></p> <p><b>Diffuser/Optics</b></p> <p><b>Light Source</b></p> <p><b>Max Watts</b></p> <p><b>Mounting</b></p> <p><b>Certification</b></p>	<p>Spun aluminum with extruded stem and stamped steel canopy*</p> <ul style="list-style-type: none"> <li>• Lensed LED (no diffuser) for Dry locations only</li> <li>• TurboLED Extra wide beam silicone optic</li> <li>• TurboLED wide beam silicone optic</li> </ul> <p>LED</p> <p>36.1</p> <p>Mounts over 4" recessed outlet box.</p> <p>Manufactured in accordance with U.L. standard 1598 -</p>
---	---

**Ordering Guide:** Choose from each category, using designated code to specify.

HLD322 STEMX					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

**Diffuser/Optics**

- Lensed LED (no diffuser)
- LOW** - Wide beam optic
- LOX** - Extra wide beam optic

**Light Source**

- TL11.0 HO** - 11.01W/40K 2310 Lm TurboLED
- TL19.4 HO** - 19.35W/40K 3620 Lm TurboLED
- TL20 COB** - 19.9W/30K 3212 Lm TurboLED
- TL22.8 HO** - 22.77W/40K 4125 Lm TurboLED
- TL23.5 COB** - 23.4W/30K 3691 Lm TurboLED
- TL26.2 HO** - 26.22W/40K 4618 Lm TurboLED
- TL27 COB** - 27W/30K 4158 Lm TurboLED
- TL29.7 HO** - 29.72W/40K 5105 Lm TurboLED
- TL31 COB** - 30.6W/30K 4613 Lm TurboLED
- TL35.0 HO** - 35.04W/40K 5811 Lm TurboLED
- TL36 COB** - 36.1W/30K 5277 Lm TurboLED

**Finish**

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded\***
- RAL** - [Specify Color #](#)
- UPG** - [Select Color from Luraline Palette](#)
- Premium\***
- CCM** - Custom Color
- CIC** - [Inner Color](#)
- CTC** - Clear Top Coat
- \* Subject to Surcharge

**Extras (Order Separately)**

- 22K** Candlelight 90+ CRI (MOQ item - NCNR)
- 27K** Non-Stock item - consult factory for availability
- 35K**
- 50K** Daylight (MOQ item - NCNR)
- DIM010** 4-wire 0-10V Dimming - 120-277V
- SSP** 10KV 120-277V Supplemental Surge Protection