



**Cutoff/downlight HLD322 STEMX** H: 13.25 W: 22 OAL: 28.75

**Description**

Helos Cutoff pendant with 12" stem and 40° swivel canopy

**Specifications**

Housing	Spun aluminum with extruded stem and stamped steel canopy*
Diffuser/Optics	Lensed LED module (no diffuser) (for use in Dry or Damp locations)
Light Source	LED
Max Watts	23.4
Mounting	Mounts over 4" recessed outlet box.
Certification	Manufactured in accordance with U.L. standard 1598 -

**Ordering Information** Choose one from each category, filling in the guide using designated code.

Guide	<u>HLD322 STEMX</u>	<u>    </u>	<u>    </u>	<u>    </u>	<u>    </u>
	MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

**Diffuser/Optics**

LED module (no diffuser)

**Light Source**

**TL20 COB** - 19.9W/30K 3212 Lm TurboLED  
**TL23 COB** - 23.4W/30K 3691 Lm TurboLED

**Finish**

**Standard**  
**BL** - Black  
**DB** - Dura-Bronze  
**WH** - White  
**Upgraded\***  
**RAL** - Specify Color #  
**UPG** - Select Color from Luraline Palette  
**Premium\***  
**CCM** - Custom Color  
**CIC** - Inner Color  
**CTC** - Clear Top Coat  
\* Subject to Surcharge

**Extras (Order Separately)**

**27K** Warm White 90+ CRI TurboLED