



Area/Bollard LA293 H: 40.5 W: 16.75

Description

This fixture takes the traditional acorn-style one step further with a design that accommodates today's concerns for managing light. With the shielded top, this fixture directing the light downward delivering where they're needed. This Acorn style light, measures 16.75" in diameter.

Specifications

- Housing** Die-cast aluminum
- Diffuser/Optics**
 - Clear Textured Acrylic
 - Clear Textured Polycarbonate
 - Frost Textured Acrylic
 - White Textured Acrylic
- Light Source** LTE
- Max Watts** 60
- Electrical** LTE - Includes 50,000 Hr. LED light engine with 120-277V constant current driver.
- Mounting** Slips 3" OD P Series Poles - Order seperately
- Certification** Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations



Ordering Guide: Choose from each category, using designated code to specify.

LA293				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

- C** - Clear Textured Acrylic
- F** - Frost Textured Acrylic
- P** - Clear Textured Polycarbonate
- W** - White Textured Acrylic

Light Source

- L4000C** - 40W/40K 4000 lumen LED
- L6000C** - 60W/40K 6000 lumen LED

Finish

- Standard**
- B** - Textured Black
- Upgraded***
- W** - Textured White
- Z** - Textured Bronze
- * Subject to Surcharge

Extras (Order Separately)

- GSS** 10 KV Ground Surge Supression (120-277V)