



Canopy LB11W H: 4.50 W: 10

Description

Polycarbonate LED Canopy Light

Specifications

Housing	Injection-molded polycarbonate
Diffuser/Optics	White Polycarbonate
Light Source	LED
Max Watts	23
Electrical	DOB - Includes 120V HPF Triac dimmable 50,000 Hr LED light engine with Driver on Board.
Mounting	Mounts over 4" recessed outlet box
Certification	Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations

Ordering Information Choose one from each category, filling in the guide using designated code.

Guide	<u>LB11W</u>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
	MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

White Polycarbonate

Light Source

- L13 DOB** - 13W/30K 910 lumen LED
- L14 DOB** - 14W/30K 1350 lumen LED
- L18 LTE 40K** - 18W/40K 1824 lumen LED
- L23 DOB** - 23W/30K 1850 lumen LED

Finish

- Standard**
- BL** - Black
- WH** - White

Extras (Order Separately)

- OSUHF** - Occupancy Sensor
Hidden behind diffuser
- PCL1** - Factory-installed 120V
PHOTOCELL - Only available
with LED Light Sources.