



Canopy LB11W H: 4.50 W: 10

Description

Polycarbonate LED Canopy Light

Specifications

Housing	Injection-molded polycarbonate	
Diffuser/Optics	White Polycarbonate	
Light Source	DOB	LTE
Max Watts	23	18
Electrical	DOB - Includes 120V HPF Triac dimmable 50,000 Hr LED light engine with Driver on Board. LTE - Includes 50,000 Hr. LED light engine with 120-277V constant current driver.	
Mounting	Mounts over 4" recessed outlet box	
Certification	Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations	



Ordering Guide: Choose from each category, using designated code to specify.

LB11W				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics
White Polycarbonate

Light Source
L13 DOB - 13W/30K 910 lumen LED
L14 DOB - 14W/30K 1350 lumen LED
L18 LTE 40K - 18W/40K 1824 lumen LED
L23 DOB - 23W/30K 1850 lumen LED

Finish
Standard
WH - White

Extras (Order Separately)
OSUHF - Occupancy Sensor
 Hidden behind diffuser
PCL1 - Factory-installed 120V PHOTOCELL - Only available with LED Light Sources.