



**Bulkhead LB1LG** H: 10.63 W: 6 E: 4.50 MC: 3

**Description**

Oval LED Bulkhead with Grille

**Specifications**

<b>Housing</b>	Stamped aluminum with polypropylene trim
<b>Diffuser/Optics</b>	Frosted Polycarbonate
<b>Light Source</b>	LED
<b>Max Watts</b>	13
<b>Electrical</b>	<b>DOB</b> - Includes 120V HPF Triac dimmable 50,000 Hr LED light engine with Driver on Board. <b>LTE</b> - Includes 50,000 Hr. LED light engine with 120-277V constant current driver.
<b>Mounting</b>	Mounts over 4" recessed outlet box.
<b>Certification</b>	Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations

**Ordering Guide:** Choose from each category, using designated code to specify.

LB1LG				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

**Diffuser/Optics**

Frosted Polycarbonate

**Light Source**

**L10 LTE 40K** - 11W/40K 912 lumen LED  
**L13 DOB** - 13W/30K 910 lumen LED

**Finish**

**Standard**  
**BL** - Black  
**WH** - White

**Extras (Order Separately)**

**PCL1** Factory-installed 120V PHOTOCELL - Only available with LED Light Sources.