



**Bulkhead LB10F** H: 10.63 W: 6 E: 4.25 MC: 3

**Description**

Oval Open Face LED Bulkhead

**Specifications**

|                        |  |
|------------------------|--|
| <b>Housing</b>         | Stamped aluminum with polypropylene trim   |
| <b>Diffuser/Optics</b> | Frosted Polycarbonate  |
| <b>Light Source</b>    | LED  |
| <b>Max Watts</b>       | 13   |
| <b>Electrical</b>      | <b>DOB</b> - Includes 120V HPF Triac dimmable 50,000 Hr LED light engine with Driver on Board. |
| <b>Mounting</b>        | Mounts over 4" recessed outlet box.  |
| <b>Certification</b>   | Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations                |

**Ordering Information** Choose one from each category, filling in the guide using designated code.

|       |              |             |              |             |             |
|-------|--------------|-------------|--------------|-------------|-------------|
| Guide | <u>LB10F</u> | <u>    </u> | <u>    </u>  | <u>    </u> | <u>    </u> |
|       | MODEL        | DIFFUSER    | LIGHT SOURCE | FINISH      | EXTRAS      |

**Diffuser/Optics**  
Frosted Polycarbonate

**Light Source**  
**L10 LTE 40K** - 11W/40K 912 lumen LED  
**L13 DOB** - 13W/30K 910 lumen LED

**Finish**  
**Standard**  
**BL** - Black  
**WH** - White

**Extras (Order Separately)**  
**PCL1** Factory-installed 120V PHOTOCELL - Only available with LED Light Sources.