



Bulkhead LB2GR H: 10.38 W: 10.38 E: 5.25 MC: 5.13

Description

Round LED Bulkhead with Guard

Specifications

Housing	Stamped aluminum with polypropylene trim
Diffuser/Optics	Frosted Polycarbonate
Light Source	LED
Max Watts	23
Electrical	DOB - Includes 120V HPF Triac dimmable 50,000 Hr LED light engine with Driver on Board.
Mounting	Mounts over 4" recessed outlet box.
Certification	

Ordering Information Choose one from each category, filling in the guide using designated code.

Guide	<u>LB2GR</u>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
	MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

Frosted Polycarbonate

Light Source

- L14 DOB** - 14W/30K 1350 lumen LED
- L18 LTE 40K** - 18W/40K 1824 lumen LED
- L23 DOB** - 23W/30K 1850 lumen LED

Finish

- Standard**
- BL** - Black
- WH** - White

Extras (Order Separately)

- OSUHF** - Occupancy Sensor Hidden behind diffuser
- PCL1** - Factory-installed 120V PHOTOCELL - Only available with LED Light Sources.

NOTES: May be wall or ceiling mounted.