



**Bulkhead LB2GR** H: 10.38 W: 10.38 E: 5.25 MC: 5.13

**Description**

Round LED Bulkhead with Guard

**Specifications**

<b>Housing</b>	Stamped aluminum with polypropylene trim
<b>Diffuser/Optics</b>	Frosted Polycarbonate
<b>Light Source</b>	LED
<b>Max Watts</b>	23
<b>Electrical</b>	<b>DOB</b> - Includes 120V HPF Triac dimmable 50,000 Hr LED light engine with Driver on Board. <b>LTE</b> - Includes 50,000 Hr. LED light engine with 120-277V constant current driver.
<b>Mounting</b>	Mounts over 4" recessed outlet box.
<b>Certification</b>	

**Ordering Guide:** Choose from each category, using designated code to specify.

LB2GR					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

**Diffuser/Optics**

Frosted Polycarbonate

**Light Source**

- L13 DOB** - 13W/30K 910 lumen LED
- L14 DOB** - 14W/30K 1350 lumen LED
- L18 LTE 40K** - 18W/40K 1824 lumen LED
- L23 DOB** - 23W/30K 1850 lumen LED

**Finish**

- Standard**
- BL** - Black
- WH** - White

**Extras (Order Separately)**

- OSUHF** - Occupancy Sensor  
Hidden behind diffuser
- PCL1** - Factory-installed 120V PHOTOCELL - Only available with LED Light Sources.

NOTES: May be wall or ceiling mounted.