



**Bulkhead LB2LG** H: 5.25 W: 10.38 E: 5.25 MC: 5-1/8

**Description**

Round LED Bulkhead with Grille

**Specifications**

<b>Housing</b>	Stamped aluminum with polypropylene trim
<b>Diffuser/Optics</b>	Frosted Polycarbonate
<b>Light Source</b>	LED
<b>Max Watts</b>	23
<b>Electrical</b>	<b>DOB</b> - Includes 120V HPF Triac dimmable 50,000 Hr LED light engine with Driver on Board.
<b>Mounting</b>	Mounts over 4" recessed outlet box.
<b>Certification</b>	Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations

**Ordering Information** Choose one from each category, filling in the guide using designated code.

Guide	<u>LB2LG</u>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
	MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

**Diffuser/Optics**

Frosted Polycarbonate

**Light Source**

**L14 DOB** - 14W/30K 1350 lumen LED  
**L18 LTE 40K** - 18W/40K 1824 lumen LED  
**L23 DOB** - 23W/30K 1850 lumen LED

**Finish**

**Standard**  
**BL** - Black  
**WH** - White

**Extras (Order Separately)**

**OSUHF** - Occupancy Sensor  
 Hidden behind diffuser  
**PCL1** - Factory-installed 120V  
 PHOTOCELL - Only available  
 with LED Light Sources.

NOTES: May be wall or ceiling mounted.