



**Bulkhead LB2LG** H: 5.25 W: 10.38 E: 5.25 MC: 5-1/8

### Description

Round LED Bulkhead with Grille

### Specifications

<b>Housing</b>	Stamped aluminum with polypropylene trim
<b>Diffuser/Optics</b>	Frosted Polycarbonate
<b>Light Source</b>	LED
<b>Max Watts</b>	23
<b>Electrical</b>	<b>DOB</b> - Includes 120V HPF Triac dimmable 50,000 Hr LED light engine with Driver on Board. <b>LTE</b> - Includes 50,000 Hr. LED light engine with 120-277V constant current driver.
<b>Mounting</b>	Mounts over 4" recessed outlet box.
<b>Certification</b>	Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations

**Ordering Guide:** Choose from each category, using designated code to specify.

LB2LG				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

#### Diffuser/Optics

Frosted Polycarbonate

#### Light Source

**L13 DOB** - 13W/30K 910 lumen LED  
**L14 DOB** - 14W/30K 1350 lumen LED  
**L18 LTE 40K** - 18W/40K 1824 lumen LED  
**L23 DOB** - 23W/30K 1850 lumen LED

#### Finish

**Standard**  
**BL** - Black  
**WH** - White

#### Extras (Order Separately)

**OSUHF** - Occupancy Sensor  
 Hidden behind diffuser  
**PCL1** - Factory-installed 120V  
 PHOTOCELL - Only available  
 with LED Light Sources.

NOTES: May be wall or ceiling mounted.