



Bulkhead LB2LG H: 5.25 W: 10.38 E: 5.25 MC: 5-1/8

Description

Round LED Bulkhead with Grille

Specifications

- Housing** Stamped aluminum with polypropylene trim
- Diffuser** Frosted Polycarbonate
- Light Source** LED
- Max Watts** 23
- Electrical** DOB - Includes 120V HPF Triac dimmable 50,000 Hr LED light engine with Driver on Board.
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations

Ordering Information Choose one from each category, filling in the guide using designated code.

Guide	<u>LB2LG</u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>
	MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser
Frosted Polycarbonate

Light Source
L14 DOB - 14W/30K 1350 lumen LED
L18 LTE 40K - 18W/40K 1824 lumen LED
L23 DOB - 23W/30K 1850 lumen LED

Finish
Standard
BL - Black
WH - White

Extras (Order Separately)
OSUHF - Occupancy Sensor
 Hidden behind diffuser
PCL1 - Factory-installed 120V
 PHOTOCELL - Only available
 with LED Light Sources.

NOTES: May be wall or ceiling mounted.