



Bulkhead LB2OF H: 10.38 W: 10.38 E: 5.25 MC: 5.13

Description

Open Face Round LED Bulkhead

Specifications

- Housing** Stamped aluminum with polypropylene trim
- Diffuser** Frosted Polycarbonate
- Light Source** LED
- Max Watts** 23
- Electrical** **DOB** - Includes 120V HPF Triac dimmable 50,000 Hr LED light engine with Driver on Board.
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations

Ordering Information Choose one from each category, filling in the guide using designated code.

Guide	LB2OF				
	MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser
Frosted Polycarbonate

Light Source
L14 DOB - 14W/30K 1350 lumen LED
L18 LTE 40K - 18W/40K 1824 lumen LED
L23 DOB - 23W/30K 1850 lumen LED

Finish
Standard
BL - Black
WH - White

Extras (Order Separately)
OSUHF - Occupancy Sensor
 Hidden behind diffuser
PCL1 - Factory-installed 120V
 PHOTOCELL - Only available
 with LED Light Sources.

NOTES: May be wall or ceiling mounted.