



Bulkhead LB2OF H: 10.38 W: 10.38 E: 5.25 MC: 5.13

Description

Open Face Round LED Bulkhead

Specifications

- Housing** Stamped aluminum with polypropylene trim
- Diffuser/Optics** Frosted Polycarbonate
- Light Source** LED
- Max Watts** 23
- Electrical** **DOB** - Includes 120V HPF Triac dimmable 50,000 Hr LED light engine with Driver on Board.
LTE - Includes 50,000 Hr. LED light engine with 120-277V constant current driver.
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations

Ordering Information Choose one from each category, filling in the guide using designated code.

Guide	<u>LB2OF</u>				
	MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

Frosted Polycarbonate

Light Source

- L14 DOB** - 14W/30K 1350 lumen LED
- L18 LTE 40K** - 18W/40K 1824 lumen LED
- L23 DOB** - 23W/30K 1850 lumen LED

Finish

- Standard**
- BL** - Black
- WH** - White

Extras (Order Separately)

- OSUHF** Occupancy Sensor
Hidden behind diffuser
- PCL1** Factory-installed 120V PHOTOCELL - Only available with LED Light Sources.

NOTES: May be wall or ceiling mounted.