



Bulkhead LB20F H: 10.38 W: 10.38 E: 5.25 MC: 5.13

Description

Open Face Round LED Bulkhead

Specifications

Housing	Stamped aluminum with polypropylene trim	
Diffuser/Optics	Frosted Polycarbonate	
Light Source	DOB	LTE
Max Watts	23	18
Electrical	DOB - Includes 120V HPF Triac dimmable 50,000 Hr LED light engine with Driver on Board. LTE - Includes 50,000 Hr. LED light engine with 120-277V constant current driver.	
Mounting	Mounts over 4" recessed outlet box.	
Certification	Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations	



Ordering Guide: Choose from each category, using designated code to specify.

LB20F					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

Diffuser/Optics

Frosted Polycarbonate

Light Source

L13 DOB - 13W/30K 910 lumen LED
L14 DOB - 14W/30K 1350 lumen LED
L18 LTE 40K - 18W/40K 1824 lumen LED
L23 DOB - 23W/30K 1850 lumen LED

Finish

Standard
BL - Black
WH - White

Extras (Order Separately)

OSUHF - Occupancy Sensor
 Hidden behind diffuser
PCL1 - Factory-installed 120V
 PHOTOCELL - Only available
 with LED Light Sources.

NOTES: May be wall or ceiling mounted.
 May be wall or ceiling mounted.
 May be wall or ceiling mounted.
 May be wall or ceiling mounted.
 May be wall or ceiling mounted.
 May be wall or ceiling mounted.